

FP861MT NEW PNEUMATIC HAND SHEAR

FP861MT. The universal cutting tool for Composites.





WHAT'S NEW:

Central back-located air exhaust +10% power +10% torque High manageability in 1100 g

RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 • 20161 Milan · Italy ph. +39 02 66 22 12 31 • fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com



TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust 6 bar nominal* (\pm 1 bar) lubricated air supply Air consumption: 9 std liters/sec* Power: 400 W at nominal air supply conditions Blade: 86 mm with hard metal counterblade Blade descr.: 86THSS, 86 mm dia., 8-edge, HSS steel Blade speed: 900 r.p.m.* Cutting ability: up to 25 mm Sound pressure: 72 dBe (EN ISO 15744)* Vibration Level: 1,36 m/sec2 (ISO 8662)* Net weight: 1100 g Total weight (with packing): 1995 g Temperature range: 0 – 55 C Umidity range: 10 – 95% without condensate

*The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), reccomended operating pressure.