

MADE IN ITALY

FP862M New PNEUMATIC HAND SHEAR

The most powerful pneumatic cutting tool for industry.







WHAT'S NEW:

New Monster foot New aggressive design

FOLLOW US:



RASOR ELETTROMECCANICA SRL Via Giannetto Mattei 41/43 20044 Arese (MI) · Italy ph. +39 02 66 22 12 31 info@rasor-cutters.com

www.rasor-cutters.com

NEW PNEUMATIC HAND SHEAR FP862M

TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust 6 bar nominal* (± 1 bar) lubricated air supply Air consumption: 9 std liters/sec* Power: 400 W at nominal air supply conditions Blade: 86 mm with hard metal counterblade Blade descr.: 86THSS, 86 mm dia., 8-edge, HSS steel Blade speed: 1400 r.p.m.* Cutting ability: up to 25 mm Sound pressure: 72 dBe (EN ISO 15744)* Vibration Level: 1,36 m/sec2 (ISO 8662)* Net weight: 1100 g Total weight (with packing): 1995 g Temperature range: 0 – 55 C Umidity range: 10 – 95% without condensate

*The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), reccomended operating pressure.







Rasor recommend to use only dry air lubricated with special Rasor VG 10 pneumatic oil

Ø8mm

minimum recommended

CE



BLADES AVAILABLE:

86PHSS, 86 mm 5-edges, HSS steel
86THSS, 86 mm 8-edges, HSS steel
86PHSSTF, 86 mm 5-edges, HSS steel
Teflon® coated | 86THSSTF, 86 mm 8-edges,
HSS steel Teflon® coated | 86THSSTN, 86 mm
8-edges, HSS steel Titanium coated | 86TMD,
86 mm 8-edges, Carbide (Widia®)